



Metafix

PRODUCT INFORMATION BULLETIN



RH-PRO 11 HVHA

HIGH VELOCITY HOT AIR STERILISER



FEATURES AND BENEFITS

- ◆ 12, 16 and 20 minute complete cycles – Door Closed to Door Open
- ◆ Accommodates small and large cassettes
- ◆ Up to 4 large instrument cassettes per cycle
- ◆ Uses 85% less energy than steam sterilisers – verified by independent research
- ◆ Does not corrode, pit or dull instruments – extending useful instrument life
- ◆ Does not use water, steam or vacuum – lower costs and maintenance
- ◆ Colour touchscreen control
- ◆ Auto locking door
- ◆ USB Port for data logger or external printer
- ◆ 3 Year inclusive parts and labour warranty
- ◆ Nationwide engineer support and service

Metafix (UK) Limited

1 Dean Close, Raunds, Northamptonshire NN9 6BD

E-mail: sales@metafix.co.uk

Tel: 01933 461907

www.metafix.co.uk

RH-PRO 11 HVHA

HIGH VELOCITY HOT AIR STERILISER



VALIDATED STERILISATION CYCLES

- ◆ **Cycle 1:** 6 minutes for unwrapped instruments
- ◆ **Cycle 2:** 8 minutes for unwrapped handpieces
- ◆ **Cycle 3:** 12 minutes for wrapped instruments and handpieces

(Door Closed to Door Open is 12, 16 & 20 minutes respectively, allowing for cycle warm up and temperature stabilisation)

INCLUDED WITH STERILISER

- ◆ 4 – Instrument trays
- ◆ 1 pair – Tray removal safety gloves
- ◆ 3 year inclusive parts and labour warranty

ACCESSORIES

- ◆ Instrument trays
- ◆ Cassette racks
- ◆ Pouch racks
- ◆ HVHA self sealing steriliser bags
- ◆ HVHA nylon sterilisation pouches (include dry heat indicator)
- ◆ HVHA nylon roll stock tubing
- ◆ HVHA table-top impulse sealers
- ◆ HVHA dry heat indicator strips
- ◆ HVHA spore test kits
- ◆ Epson TM-U220B printer with auto cutter

SPECIFICATIONS

- ◆ Unit size (OD) 572(W) x 572(D) x 495(H) mm
- ◆ Chamber size (ID) 279(W) x 433(D) x 299(H) mm
- ◆ Chamber capacity 38 litres
- ◆ Weight Unit 34Kg
- ◆ Instrument tray size 4 trays each: 229(W) x 381(D) x 28(H) mm; 9”(W) x 15”(D) x 1”(H)
- ◆ Electrical 220–240V, 1400W warm up, 300W operating
- ◆ Sterilization temperature 190°C
- ◆ Load capacity 3.2Kg validated
- ◆ Manufactured by CPAC Equipment Inc. USA to FDA QSR/ISO13485
- ◆ Approvals CE 0197 TUV Rhineland, FDA 510(K) K881371, TUV Electrical/EMI Safety

Metafix (UK) Limited

1 Dean Close, Raunds, Northamptonshire NN9 6BD

E-mail: sales@metafix.co.uk

Tel: 01933 461907

www.metafix.co.uk